

## Material Safety Data Sheet

#### SECTION I - COMPANY IDENTIFICATION

PRODUCT: ACTI-BRITE CAT. NO .:

AB-1, AB-5, AB-55

MANUFACTURED BY:

**TELEPHONE NUMBERS:** Office:

Virginia KMP Corporation 4100 Platinum Way Dallas, Texas 75237

1-(214) 330-7731 Emergency Only: 1-(800) 424-9300

#### **SECTION II - HAZARDOUS INGREDIENTS**

OSHA Hazardous Components (29 CFR 1910.1200)

**EXPOSURE LIMITS: 8 HR. TWA** 

**OSHA PEL** 

**ACGIH TLV** 

Phosphoric acid (CAS# 7664-38-2) Hydrofluoric acid (CAS# 7664-39-3) 1 mg/m<sup>3</sup>

1 mg/m<sup>3</sup>

STEL

3 mg/m<sup>3</sup> 3 ppm (F) STEL 3 mg/m3 CL 3 ppm (F)

STEL

6 ppm (F)

**SECTION III - HAZARDS IDENTIFICATIONS** 

EMERGENCY OVERVIEW: DANGER! Corrosive to all body tissues. Avoid contact with skin or eyes. Harmful if inhaled or swallowed.

POTENTIAL HEALTH EFFECTS:

INHALATION:

Inhalation of vapor or mist is corrosive to respiratory tract. Symptoms include coughing, wheezing, laryngitis, shortness of breath, headache, nausea, and vomiting.

EYE CONTACT:

Liquid or vapors are corrosive to eyes. Immediate irritation followed by destruction of tissue.

SKIN CONTACT:

This material is corrosive to all body tissues. Full extent of damage may not be apparent for 12 - 24 hours after exposure.

Severe burns are slow healing. Gangrene may follow damage.

INGESTION:

Corrosive, moderately toxic, causes nausea, vomiting, loss of consciousness.

CHRONIC Effects: Damage to kidneys and liver (phosphoric acid). Changes in bones or joints (hydrofluoric acid).

NOTE:

CARCINOGENICITY: LISTED IN NTP? No

IARC? No

OSHA Regulated? No

#### SECTION IV - FIRST AID MEASURES

INHALATION:

Remove victim to fresh air and, if needed, immediately begin artificial respiration. Give oxygen if breathing is labored. Get emergency

medical help. Contact a physician immediately.

**EYE CONTACT:** 

Flush eyes with water for 15 minutes. Get medical attention.

SKIN CONTACT:

Flush with water or soap and water for 15 minutes or until all traces have been removed. Seek medical attention if symptoms develop and

persist.

INGESTION:

Do not induce vomiting. Rinse mouth out with water. Get immediate medical attention.

## SECTION V - FIRE FIGHTING MEASURES

FLASHPOINT (TEST METHOD):

None

FLAMMABLE LIMITS:

LOWER: NA

UPPER: NA

**AUTOIGNITION TEMPERATURE: NA** 

**GENERAL HAZARD:** 

Toxic fumes produced in fire.

FIRE FIGHTING INSTRUCTIONS:

Approach fire from upwind side. Avoid breathing smoke, fumes, mist, or vapors on the downwind side. Firefighters

wear protective clothing and self contained breathing apparatus.

**EXTINGUISHING MEDIA:** 

Dry powder, carbon dioxide (CO<sub>2</sub>), water fog or spray.

**HAZARDOUS COMBUSTION PRODUCTS:** 

Smoke, irritating vapors, toxic fumes of POx, and corrosive F fumes, CO, CO2.

# SECTION VI - ACCIDENTAL RELEASE MEASURES

LAND SPILL:

Emergency response coordinator must have mandated training, Eliminate all ignition sources. SMALL SPILLS: Pick up with absorbent materials and place in non-leaking containers; seal tightly for proper disposal or reuse. LARGE SPILLS: Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak if safe to do so. Dike and contain, Remove with vacuum trucks or pump to storage/salvage vessels.

WATER SPILL:

Notify proper authorities.

Clean up leaks/spills immediately to prevent soil or water contamination.

### **SECTION VII - HANDLING AND STORAGE**

HANDLING:

Avoid contact with skin, eyes, and clothing. After handling this product, wash hands before eating, drinking or smoking. If contact

occurs, remove contaminated clothing. If needed, take first aid action shown in section IV. Launder contaminated clothing before reuse.

STORAGE:

Store away from food stuffs, alkaline materials

### **ACTI-BRITE**

### SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation recommended.

PERSONAL PROTECTION: If TLV is exceeded wear NIOSH approved respirator. Use heavy rubber type gloves, full face shield and boots, aprons, drench

showers, eye wash as needed for protection against spills and/or splashes.

#### SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE: ND SPECIFIC GRAVITY (H<sub>2</sub>O=1): 1.15 SOLUBILITY IN WATER: Complete VAPOR DENSITY (Air=1): >1
EVAPORATION RATE (BuAc=1): >1

VOC: 0%

pH: <2.0

FREEZING POINT: ND

POILING POINT: 313

**BOILING POINT: 212 F** 

APPEARANCE & ODOR: Pink liquid, pungent odor.

# SECTION X - STABILITY AND REACTIVITY

STABILITY:

Stable.

CONDITIONS TO AVOID:

High temperatures.

MATERIALS TO AVOID: Alkaline materials

Alkaline materials, may react with metals to produce hydrogen gas.

HAZARDOUS DECOMPOSITION PRODUCTS: Corrosive F fumes, toxic PO<sub>x</sub> fumes, from combustion - smoke, CO, CO<sub>2</sub>.

HAZARDOUS POLYMERIZATION: Will not occur.

# SECTION XI - TOXICOLOGICAL INFORMATION

LDLo: Phosphoric Acid 220 mg/kg (unr - man) LD50: 1530 mg/kg (oral - rat) LD50: 2740 mg/kg (skin - rat) Hydrofluoric Acid 50 ppm / 30 M LCLo: (inh - human) LC50: 966 ppm / 1 hr (inh - rat) TCLo: 100 mg/m3 (inh - human) NOSE, EYE, PUL

SECTION XII - ECOLOGICAL INFORMATION

Harmful to aquatic life in very low concentrations.

Phosphoric Acid

138 ppm / 24 hr / mosquito fish / TLm / fresh water

Hydrofluoric Acid 60 ppm / fish / lethal / fresh water

# **SECTION XIII - DISPOSAL CONSIDERATIONS**

Dispose as hazardous waste. Classification and documentation is required before disposal. Follow all local, state and federal regulations.

# SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Corrosive liquid, Acidic, Inorganic, n.o.s. (contains phosphoric acid, hydrofluoric acid), 8, UN3264, PG II

HAZARD CLASS: 8
IDENTIFICATION NUMBER: UN3264

DOT Emergency Guide #:

59

Reportable Quantity (RQ):

65 gallons (hydrofluoric acid)

International:

Corrosive liquid, Acidic, Inorganic, n.o.s. (contains phosphoric acid, hydrofluoric acid), 8, UN3264, PG II, IMDG 8147-1

#### SECTION XV - REGULATORY INFORMATION

TSCA (Toxic Substance Control Act): Components of this product are listed on the TSCA Inventory.

CERCLA (Comprehensive Environmental Response, Compensation and Liability Act): Reportable quantity is 65 gallons (hydrofluoric acid). Contact

local authorities for other reporting requirements.

SARA TITLE III (Superfund Amendments and Reauthorization Act):

Section 302 Thr

Threshold Planning Quantity is 65 gallons (hydrofluoric acid)

Section 313

Hydrogen Floride

Phosphoric Acid

(CAS# 7664-39-9) (CAS# 7664-38-2) 8 - 15% 5 - 10%

**CALIFORNIA PROPOSITION 65:** 

Not listed.

# SECTION XVI - OTHER INFORMATION

State Right-to-Know Programs: MA, NJ, PA

NFPA Ratings

Health: Flammability: 4

Reactivity:

0

HMIS Protective Equipment:

X See your supervisor

Prepared by: Virginia KMP Corporation

revised 9/27/96

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Virginia KMP. The data on this sheet related only to specific material designated here in. Virginia KMP assumes no legal responsibility for use or reliance upon these data.