

MATERIAL SAFETY DATA SHEET

SECTION I - PRODUCT IDENTIFICATION

Manufacturer: DIY Products
2825 West 31st Street
Chicago, IL 60623

Date: 02/01/94

Information Phone: 1-312-247-6000


Emergency Phone: 1-312-247-6000

Product Class:	Paint related material	Hazard Ratings:	Health:	
Trade Name:	Oops Latex Paint Remover		Fire:	
Product Code:	#744, #802, #834, #835 & #755		Reactivity:	
C.A.S. Number:	mixture			

SECTION II - HAZARDOUS INGREDIENTS

Ingredients	CAS #	% Weight	Exposure Limits			Vapor Pressure
			ACGIH/TLV	OSHA/PEL	OTHER	
Emchlor 1/Haslo 99			50ppm	50ppm		
Filmex C 200 Proof Alcohol	67-56-1		1000ppm	1000ppm		
Xylene	1330-20-7		100ppm	100ppm		
V M & P			300ppm	300ppm		

SECTION 313 SUPPLIER NOTIFICATION:



SECTION III - PHYSICAL DATA

Boiling Range:	162 Deg F	Vapor Density:	air
Evap. Rate:	not available	Liquid Density:	not available
Volatiles Volume:	100%	Wgt Per Gallon:	6.676 lb/gal
Appearance:	water-white liquid with a characteristic odor	Spec. Gravity:	0.8014

Page: 1

DIYP-00-0001.01

MATERIAL SAFETY DATA SHEET

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Class:	N/A	Flash Point:	45 Deg F	LEL:	
---------------------	-----	--------------	----------	------	--

EXTINGUISHING MEDIA:

CO 2, Dry Chemical, Foam

SPECIAL FIREFIGHTING PROCEDURES:

Wear self contained breathing gear and protective clothing. Cool sealed drums with water spray to lesson chance of rupture. Direct water jet will spread burning material.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Material is extremely flammable. Combustion products are very toxic and highly irritating.

SECTION V - HEALTH HAZARD DATA

PERMISSIBLE EXPOSURE LEVEL:

See Section II.

EFFECTS OF OVEREXPOSURE:

EYES:	Contact irritation.
SKIN:	Contact irritation.
BREATHING:	May cause nausea, headache, dizziness and irritation of respiratory tract.
SWALLOWING:	

FIRST AID:

EYES:	Flush with water - contact a physician.
SKIN:	Wash with soap and water.
SWALLOWING:	
INHALATION:	Provide fresh air, oxygen or artificial respiration as needed. NOTE TO PHYSICIAN: THE USE OF EPINEPHRINE IS CONTRAINDICATED.

SECTION VI - REACTIVITY DATA

STABILITY:	<input type="checkbox"/>]	Unstable	<input checked="" type="checkbox"/> X]	Stable
HAZARDOUS POLYMERIZATION:	<input type="checkbox"/>]	May Occur	<input checked="" type="checkbox"/> X]	Will not occur

INCOMPATIBILITY:

Strong oxidizers, acids, bases, and "white" metals.

CONDITIONS TO AVOID:

HAZARDOUS DECOMPOSITION PRODUCTS:

HCl and other chlorinates. Hazardous Polymerization: will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Eliminate of all sources of ignition. Permit only properly protected workers in the area (i.e. with eye/skin protection and self contained breathing gear). Absorb small spills with inert absorbant. Pump large spills into salvage tank.

WASTE DISPOSAL METHOD:

Contact federal, state, and local agencies to insure compliance of disposal method with current regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

Above PEL/TLV, use NIOSH/MSHA approved respirator for organic vapors.