

MATERIAL SAFETY DATA SHEET

PARKS
Varnish Sanding Sealer

SECTION I PRODUCT INFORMATION

MSDS DATE: 09/30/85
MANUFACTURERS NAME: Parks Corporation
ADDRESS: P.O. Box 5
Somerset, MA 02726
EMERGENCY PHONE NUMBER: (508) 679-5938
DISTRIBUTOR:
CHEMICAL NAME: Alkyd Sanding Sealer
FORMULA:
PART NUMBER: 36866
CATEGORY:
BRIEF DESCRIPTION:

SECTION II HAZARDOUS INGREDIENTS & EXPOSURE LIMITS

HAZARDOUS COMPONENT(S)	CAS #	%	LIMIT VALUES
mineral spirits	64741-41-9	15.00	
min naphtha	64742-48-9	70.00	

SECTION III TYPICAL PHYSICAL PROPERTIES

BOILING POINT: 325° F.
VAPOR PRESSURE: @ 25°C 29
VAPOR DENSITY: Heavier
SOLUBILITY IN WATER: Negligible
APPEARANCE AND ODOR: Brownish, opaque, aliphatic odor
SPECIFIC GRAVITY: 0.840
% VOLATILE/VOLUME: 68
pH:
MISC. INFORMATION:

***** NFPA RATINGS *****
HEALTH = 0 FLAMMABILITY = 0 REACTIVITY = 0 SPECIAL HAZARD =

Varnish Sanding Sealer

SECTION IV FIRE & EXPLOSION HAZARD DATA

FLASH POINT: 45° F.

FLAMMABLE LIMITS:

LOWER EXPLOSIVE LIMIT (LEL): 0.9

UPPER EXPLOSIVE LIMIT (UEL): 6.0

EXTINGUISHING MEDIA:

Foam, Dry chemical, CO₂, Water spray or fog.

SPECIAL FIRE FIGHTING PROCEDURES:

Cool exposed containers with water to reduce pressure. Fight as a volatile liquid fire. self-contained breathing apparatus for fire fighters.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Keep containers tightly closed. Isolate from heat, sparks and flame.

SECTION V HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE

EYES:

May cause irritation.

SKIN:

May cause irritation leading to dermatitis.

INGESTION:

No information given by manufacturer.

INHALATION:

May result in dizziness and headaches and even unconsciousness.

FIRST AID PROCEDURES

EYE CONTACT:

Flush with water for 15 minutes. If irritation persists, obtain medical attention.

SKIN CONTACT:

Flush with water for 15 minutes. If irritation persists, obtain medical attention. Remove contaminated clothes and wash before reuse. Wash skin with soap and water.

INGESTION:

Do not induce vomiting. Call a doctor at once.

INHALATION:

Remove the victim to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Seek medical help at once.

Varnish Sanding Sealer

SECTION VI REACTIVITY DATA

STABILITY: Stable
HAZARDOUS POLYMERIZATION: Will not occur
CONDITIONS TO AVOID:
Keep away from all sources of ignition. Keep away from hot surfaces.
INCOMPATIBILITY (materials to avoid):
Strong oxidants like liquid chlorine and concentrated oxygen.
HAZARDOUS DECOMPOSITION PRODUCTS:
Carbon Monoxide in the case of incomplete combustion.

SECTION VII SPILL OR LEAK PROCEDURES / WASTE DISPOSAL

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
Remove all ignition sources. Recover free liquid. Add absorbant to area of spill. Avoid breathing vapors. Ventilate the area. Open all windows and doors. Keep petroleum products out of sewers, streams and waterways. For large spills use an absorbent such as clay, earth, sand and other floor absorbents.
WASTE DISPOSAL:
Dispose of by supervised incineration or in a chemical disposal area. Disposal must be in accordance with Federal, State, and Local regulations.

SECTION VIII . SPECIAL PROTECTION

LOCAL EXHAUST: Face velocity less then 60 fpm.
SPECIAL EXHAUST: Use only adequate ventilation.
OTHER EXHAUST: No smoking or open lights.
MECHANICAL: Explosion: proof-ventilation equipment.
PROTECTIVE GLOVES: Chemical resistant gloves.
EYE PROTECTION: Safety glasses.
OTHER PROT. EQUIPMENT: Insoluble apron if needed.
RESPIRATORY PROTECTION: Hydrocarbon vapor canister or air supplied air hose mask if needed.
VENTILATION:

Varnish Sanding Sealer

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS IN HANDLING AND STORAGE:

Keep containers closed. Keep away from heat, sparks and open flame.
Keep away from all other sources of ignition.

OTHER PRECAUTIONS:

Avoid breathing vapors. Avoid prolonged or repeated contact with skin. remove contaminated clothing. wash skin with soap and water after each use.

ADDITIONAL INFORMATION TO ADD ABOUT PRODUCT:

Adequate ventilation means ventilation equivalent to outdoors.

While this information and recommendation set forth herein are believed to be accurate as of the date hereof, Corbus Inc. makes no warranty of fitness for a particular purpose with respect hereto and disclaims all liabilities from reliance thereon.