

SECTION VI - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:  
SKIN CONTACT: Excessive exposure causes irritation.  
EYE CONTACT: Causes redness, itching or burning sensation.  
INHALATION: Excessive exposure may cause headache, dizziness, nausea, and loss of coordination. Extreme overexposure may result in unconsciousness and possibly death.

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION EYES  
MEDICAL CONDITIONS PRONE TO OVEREXPOSURE:  
None known.

TARGET ORGANS AFFECTED:  
Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

CARCINOGENICITY:  
IARC - No NTP - No OSHA - No

EMERGENCY AND FIRST AID PROCEDURES:  
SKIN CONTACT: Wash thoroughly with soap and water. Remove contaminated clothing and launder before reuse. EYE CONTACT: Immediately flush with water for 15 minutes. Get medical attention. INHALATION: If affected, remove to fresh air. Restore breathing and keep victim warm and quiet. INGESTION: Get medical attention.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:  
Remove all sources of ignition. Ventilate and remove with inert absorbent.

WASTE DISPOSAL METHOD:  
Do not puncture or incinerate container. Depressurize container and dispose of in accordance with local, state and federal regulations.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION:  
Wear a NIOSH/MSHA organic vapor/particulate respirator if exposure limits are exceeded.

VENTILATION:  
Local exhaust is preferable, general exhaust is acceptable if exposure is maintained below applicable limits.

PROTECTIVE GLOVES:  
For prolonged or repeated contact, wear chemical resistant gloves.

EYE PROTECTION:  
Wear ANSI approved safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT:  
None necessary.

HYGIENIC PRACTICES:  
WASH HANDS BEFORE EATING OR USING THE WASHROOM. SMOKE ----  
IN SMOKING AREAS ONLY.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:  
Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid skin and eye contact. Do not take internally. Keep away from heat and open flame. Contents under pressure. Do not puncture or incinerate container. Do not store in temperatures above 120°F.

OTHER PRECAUTIONS:  
Keep out of reach of children. Read entire label prior to use.

SECTION X - OTHER INFORMATION

|                                |   |              |  |
|--------------------------------|---|--------------|--|
| HEALTH FLAMMABILITY REACTIVITY | 2<br>2<br>0   | PREPARED BY: | Heather Buck<br>Drummond American Corporation<br>600 Corporate Woods Parkway<br>Vernon Hills, Illinois 60061 |
| TIV                            | Threshold Limit Value                                 | NO           | No Data  |
| PEL                            | Permissible Exposure Level                            | LEL          | Lower Explosive Level  |
| NFPA                           | National Fire Protection Association                  | HE           | Hot Established  |
| CAS                            | Chemical Abstract Service                             | PPH          | Parts Per Million  |
| NTP                            | National Toxicology Program                           | D.O.T.       | Department of Transportation   |
| OSHA                           | Occupational Safety and Health Admin.                 | N/A          | Not Applicable   |
| IARC                           | International Agency for Research on Cancer           | H*3          | Approximate milligrams of substance per cubic meter of air   |
| STEL                           | Short Term Exposure Limit, duration is for 15 minutes |              |  |

---NFPA HAZARD INDEX---

SEVERE HAZARD 4

SERIOUS HAZARD 3

MODERATE HAZARD 2

SLIGHT HAZARD 1

NO HAZARD 0

MATERIAL SAFETY DATA SHEET  
ESSENTIALLY SIMILAR TO OSHA FORM 174

QUICK PEEL  
DA 6671

MATERIAL SAFETY DATA SHEET  
ESSENTIALLY SIMILAR TO OSHA FORM 174

QUICK PEEL  
DA 6671

MANUFACTURED FOR:  
Drummond American Corporation  
600 Corporate Woods Pkwy.  
Vernon Hills, IL 60061

IN CASE OF EMERGENCY CALL:  
ROCKY MOUNTAIN POISON & DRUG CENTER  
COLLECT AT: (303) 623-5716

DATE OF PREPARATION:  
10/01/01

INFORMATION TELEPHONE NUMBER  
(847) 913-9313

SECTION I - IDENTITY

PRODUCT NUMBER DA 6671  
PRODUCT NAME QUICK PEEL  
PRODUCT CLASS SOLVENTS

SECTION II - INGREDIENTS

| INGREDIENT     | CAS NUMBER  | %     | ACGIH |      | MG/<br>M <sup>3</sup> | PEL<br>PPM | STEL<br>PPM |
|----------------|-------------|-------|-------|------|-----------------------|------------|-------------|
|                |             |       | TLV   | PPM  |                       |            |             |
| D. LIMONENE    | 5989-27-5   | 90-95 | NE    | NE   | NE                    | NE         | NE          |
| FRAGRANCE      | PROPRIETARY | 1-5   | NE    | NE   | NE                    | NE         | NE          |
| CARBON DIOXIDE | 124-38-9    | 1-5   | 5000  | 5000 | 5000                  | 5000       | NE          |

S.A.R.A. TITLE III, SECTION 313:  
THIS PRODUCT CONTAINS NO LISTED  
CHEMICALS SUBJECT TO REPORTING.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT (degrees F): < 0° - 412°F  
VAPOR DENSITY: Heavier than air  
EVAPORATION RATE: Faster than ether  
PERCENT VOLATILE (By Weight): 93.900 WEIGHT PER GALLON (LBS): 7.06

OPTIONAL INFORMATION:  
Appearance / Odor: Clear yellow liquid with orange scent  
Specific Gravity: 0.85  
VOC % (By weight): 93.99 (less federally exempt solvents)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION: U.N. CLASSIFICATION:  
OSHA CLASS N/A PER DOT N/A  
DOT CLASS ORM-D PER IMDG N/A

FLASH POINT: 115°F

LEL: 0.7

UEL: 7.0

METHOD: TAG CLOSED CUP

AEROSOL PRODUCT: TREAT AS A CYLINDER OF COMPRESSED GAS

EXTINGUISHING MEDIA: FOAM CO2 DRY CHEMICAL

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Isolate from heat, electrical equipment, sparks and open flame.  
Containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions, overexposure may not be immediately apparent. Obtain medical attention.

SPECIAL FIREFIGHTING PROCEDURE:

Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

SECTION V - REACTIVITY DATA

STABILITY: STABLE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

HAZARD DECOMPOSITION PRODUCTS:

Carbon dioxide and carbon monoxide by burning.

CONDITIONS TO AVOID:

None known.

INCOMPATIBILITY (MATERIALS TO AVOID):

None known.

D.O.T. EMERGENCY RESPONSE INFORMATION:

\*\*\* NOT APPLICABLE \*\*\*