

678800,683647

CITGO Petroleum Corporation P.O. Box 3758 Tulsa, Oklahoma 74102

684290, 89876,89878,89880,89881,89877, Material Safety Data Sheet

Trade Name:

Still 2-Cycle Oil

Commodity Code:

25-418

Synonyms:

Lubricating Oil

Date: August 24, 1990

CAS No .:

Mixture

Technical Contact: (918) 495-5933

(Refer to Section 1)

Medical Emergency: (318) 491-6215 Chemirec Emergency: (800) 424-9300

Citgo Index No.: 1215

Material Hazard Evaluation

(Per OSHA Hazard Communication Standard [29 CFR Part 1910.1200]) (OHCS)

Health: Non-Hazardous (OHCS).

Precautionary Statement: Combustible Liquid.

HMIS Rating':

Health 0

Flammability 2

Reactivity 0

1.0 Generic Composition / Components

Components Refined Petroleum Oil(s)	<u>CAS #</u> 64741-88-4 64742-01-4	<u>%</u> 70-85	Hazard Data Oral LD50(rat): > 15g/kg Eye: Practically Non-Irritating Denmal: Practically Non-Irritating Ibln LC50/4H(rat): > 5,000mg/m ³
Mineral Spirits	8052-41-3	< 15	Oral LDLo(human): > 10ml Skin: Mild irritant Eye: Mild irritant
Ashless Dispersant Package	Mixture	< 10	Eye: Minor Imitant Dennal: Minor Imitant
Rust Inhibitor	Mixture	<1	Oral LD50(rat): 60.3g/kg
Dye	Mixture	< 0.1	Dermal: Mild irritant

TORO-00-0001.01

NA - Not Applicable

ND - No DIE

אב אמ בצואום

¹ Hazard Rating: 1cast-0; slight-1; moderate-2; high-3; extreme-4 Gigo assignment based on our evaluation per NFPA and NPCA guidelines.

2.0 Physical Data

Physical Hazard Classification (Per 29 CFR Part 1910.1200)

Yes	Combustible	No	Flammable	No	Руторьогіс
No	Compressed Gas	. No	Organic Peroxide	No	Reactivity
No	Explosive	No	Oxidizer	Yes	Stable

Boiling Point, 760 mmHg. °C(°F): $\sim 160(\sim 320)$

Specific Gravity (60/60°F) (H,O. = 1): 0.87

Vapor Density (Air = 1): >1 % Volatiles by Volume: < 20

Melting Point, °C(°F): NA
Vapor Pressure, mmHg (25°C): <20
Solubility in H,O., % by Weight: Negligible
Evaporation Rate (Butyl Acetate = 1): <1 pH of Undiluted Product: ND

Appearance and Odor: Blue liquid, slight odor of petroleum distillate

Fire and Explosion Data

Flash Point, COC, °C(°F)	88(190)	
Flash Point, PMC, °C(°F)	79(174)	
Fire Point, COC, *C(*F)	105(221)	
NFPA Rating	Health: 0 Flammability: 2 Reactivity: 0	
Flammable Limits (% by volume in air)	Lower: 1.0 Upper: 6.0	
Extinguishing Media	CO_ dry chemical, foam, water fog	
Special Fire Fighting Procedure	None.	
Unusual Fire or Explosion Hazard	Water may cause frothing	

4.0Reactivity Data

Stability: Stable.

Conditions Contributing to Instability:

None

Incompatibility: Strong oxidants.

Hazardous Decomposition Products:

CO_r (CO under incomplete combustion)

(thermal, unless otherwise specified)

Conditions Contributing to Hazardous

Polymerization: None.

² Hazard Rating: least-0; slight-1; moderate-2; high-3; extreme-4 Gigo assignment based on our evaluation per NFPA guidelines.

5.0 Spill or Leak Procedures

Procedures if Material is Spilled:

- Remove sources of heat or ignition, provide adequate ventilation, contain leak.
- Small Spills: Absorb with suitable material such as rags, straw or sand.
- Large Spills: Contain spill in earthen dikes for later recovery.
- Report spills as required to appropriate authorities.

Waste Disposal:

- It is the responsibility of the user to determine if the material is a hazardous waste at the time of disposal.
- Check before disposing to be sure you are in compliance with all applicable laws and regulations.
- Chemtree/RCRA Emergency Hotline Number: 800-424-9346.

Protective Measures During Repair and Maintenance of Contaminated Equipment:

- Refer to Section VII Special Protection Information.
- Avoid prolonged contact with oil.
- Wash exposed skin thoroughly with soap and water.
- Remove soiled clothing.
- Use polymer gloves if extended, direct contact is expected.

6.0 Health Hazard Data

Health Hazard Classification

(Per 29 CFR Part 1910.1200)

No	Carcinogen	No	Corrosive	
Nο	Animal Carcinogen	No	Imitant	
No	Suspect Carcinogen	No	Sensitizer	
No	Mutagen	No	Teratogen	-
No	Highly Toxic	No	Target Organ	-
No	Toxic		1	

Product listed as Carcinogen or Potential Carcinogen by:

NTP No LARC No OSHA No Other No

Toxicity Summary: Slightly toxic on ingestion. Lethal dose for 150 lb. human adult may be 10 to 250 ml.

Major Route(s) of Entry: Inhalation of incidental mists or vapors.

Acute Exposure Symptoms

Inhalation:

Low risk of inhalation. In enclosed spaces or when hot, vapors may reach concentrations sufficient to cause drowsiness, dizziness, headache, nausea, or

lung irritation. Mists above TLV may cause chemical pneumonitis.

Dermal Contact:

Mild temporary irritant.

Eye Contact:

Mild temporary irritant.

Ingestion

Toxicity is relatively low. On ingestion of large quantities, slight GI discomfort, diarrhea, and headache may occur. Small doses may produce irritation

and diamhea.

Injection

Subcutaneous or intramuscular injection should be considered as a medical

emergency.

Chronic Exposure

Prolonged and/or frequent dermal contact may cause drying, cracking (dermatitis) or folliculitis and some components may be absorbed. Chronic inhalation of high vapor concentrations above the TLV may have neurotoxic or myelotoxic effects.

Other Special Effects

None expected.

Medical Conditions Aggravated by Exposure

None.

First Aid and Emergency Procedures for Acute Effect

Inhalation:

Remove to fresh air. Respiratory support, if necessary. Seek medical aid.

Dermal:

Wash with soap and water. Do not wear heavily contaminated clothing before

laundering.

Eyes:

Flush with large volumes of water. Seek physician if any complications arise.

Ingestion:

Do not induce vomiting. Seek medical aid.

Injection:

Subcutaneous injection is a medical emergency. Seek medical aid immediately.

Notes to Physician: Following ingestion at a Saybolt viscosity of about 330 SUS (100°F), there still exists some risk of aspiration into the lungs. Removal by cuffed tube lavage may be considered. Aspirated material may cause chemical pneumonitis or lipoid pneumonia. Subcutaneous or intramuscular injection requires prompt surgical debridement. If not familiar with technique, seek skilled advice.

9.0 Environmental Data

Product Name Commodity Code:

Lawn Boy 2-Cycle Oil

SARA TITLE III

Section 313 - Toxic Chemicals

This product does not contain toxic chemicals of Section 313 of Title III of Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

Components

CAS#

%

None

Section 311 - Hazard Categories

No Not Applicable

No Acute (limmediate Health Hazard)
No Chronic (Delayed Health Hazard)

Yes Fire Hazard

No Sudden Release of Pressure Hazard

No Reactive Hazard

Section 302/(A) - Extremely Hazardous Substances

(RQ = Reportable Quantity)

(TPQ = Threshold Planning Quantity)

This product does not contain Extremely Hazardous Substances of Section 302/(A).

Component None CAS

%

RO lbs.

TPO lbs.

Clean Water Act

Under Section 311 (b) (4) of the Clean Water Act, discharges of crude oil and petroleum products in any kind or form to surface waters must be immediately reported to the National Response Center. 800-424-8802.

Comprehensive Environmental, Response, Compensation & Liability Act (CERCLA) - Section 102 Hazardous Substances

Component None

CAS

%

RO lbs.

Petroleum and petroleum fractions are excluded from the list of CERCLA hazardous substances by Section 101(14) of CERCLA.

New Jersey Worker and Community Right-to-Know Act

Petroleum Oil

7.0 Special Protection Information

Vensilation Requirements:

Use in well ventilated area. In confined space, mechanical ventilation may be required to keep levels of certain components below mandated standards, as evaluated by designated personnel.

Permitted Air Threshold Concentration:

NIOSH Recomm. by Supplier OSHA Crit. Mineral Spirits TWA: 350 mg/m³ 100 ppm ND STEL: ND ND ND ND ND Ceil., Peak: ND

Specific Personal Protective Equipment:

Respiratory:

Normally none required. If high vapor or mist concentrations ex-

pected, use respirator approved for organic vapors and mists.

Eves:

Safety goggles, or chemical splash goggles if splashing is anticipated.

Dermal:

Oil impervious gloves if frequent or prolonged contact is expected.

Other Clothing or Equipment:

Wear body-covering work clothes to avoid prolonged or repeated exposure. Launder soiled work clothes before reuse.

8.0 Transportation and Special Precautions

Storage:

Store below 150°F. Do not apply high heat or flame to container. Keep separate from strong

oxidizing agents.

Caution:

Empty containers may contain product residue which could include flammable or explosive

vapors.

Consult appropriate Federal, State and Local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.

DOT Information

Proper Shipping Name:

Hazard Class:

Hazard Identification Number:

Placard:

Coast Guard, CHRIS Code:

Compatability Category:

Petroleum Lubricating Oil.

Combustible Liquid.

NA 1270.

Combustible Liquid.

OMT

Group 33.

10.0 Labeling

CAUTION

Combustible liquid.

Contains petroleum distillates.

Keep away from heat and flame.

Avoid excessive inhalation of fumes.

Do not permit excessive dermal contact.

Harmful or fatal if swallowed.

Do not induce vomiting.

Call a physician immediately.

Keep out of reach of children.

ALL STATEMENTS, INFORMATION, AND DATA PROVIDED IN THIS MATERIAL SAFETY DATA SHEET ARE BELIEVED TO BE ACCURATE AND RELIABLE, BUT ARE PRESENTED WITHOUT CUARANTEE, REPRESENTATION, WARRANTY, OR RESPONSIBILITY OF ANY KIND, EXPRESSED OR IMPLIED. ANY AND ALL REPRESENTATIONS AND/OR WARRANTIES OF MERCHANTIBILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY DISCLAMED. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE. NOTHING CONTAINED HEREIN IS INTENDED AS PERMISSION, INDUCEMENT, OR RECOMMENDATION TO VIOLATE ANY LAWS OR TO PRACTICE ANY INVENTION COVERED BY EXISTING PATENTS, COPYRIGHTS OR INVENTIONS.

NA - Not Applicable

ND No Date

אב - אית בבששמ

Lawn Boy Z-Cycle Oil (25-418, August 24, 1990 CIN #: 1215)

Page 7 of 7

		•	